


APTURA™ LT30 SRL Product Specification



Materials

Housing:	High-impact thermoplastic
Bumpers:	Impact-absorbing urethane
Frame:	Alloy Steel
Hub:	Aluminum Alloy
Braking Mechanism:	Carbon Steel
Lifeline:	1.25" (3.17 cm) Polyester
Snaphook:	Steel and Aluminum options available

Technical

Maximum Working Load:	400 pounds (181.43 kg)
Minimum Breaking Strength:	3000 pounds (13.34 kN)
Lifeline Tension:	2 to 6 pounds (8.8 N to 26.6 N)
Maximum Arresting Distance:	42" (60.96 cm) for workers 310 lbs. (140.61 kg) and under 54" (1.06 m) for workers 311 lbs. - 400 lbs. (141.06 kg - 181.43 kg)
Arresting Force:	900 lbs (4 kN) for workers 310 lbs. and under (140.61 kg) 1800 lbs (8 kN) for workers 311 lbs. - 400 lbs. (141.06 kg - 181.43 kg)
Weight:	7.5 pounds (3.38 kg)
Maximum line length:	30 feet (9 m)* *Available in lengths from 13' (3.9 m) to 30' (9 m) in 1' (.3 m) increments

Certification

This product meets or exceeds the following standards:
OSHA: 1926.502, 1910.66
ANSI: A10.14, Z359.1
CSA: Z259.2.2-98 Type 2

