

VENTED HARD HAT



Features

- ▶ Six large cooling vents along the crown improve air circulation and comfort by reducing heat buildup (Patent Pending).
- ▶ Patented easy-to-adjust ratchet design for added comfort and convenience.
- ▶ Special rain gutter along bottom edge helps reduce water dripping on neck.
- ▶ Low profile and lightweight design for comfort over long periods .
- ▶ Lateral contours above the ear for easy integration of hearing protection
- ▶ Patented Glaregard™ underbrim reduces reflective glare from the sun.
- ▶ Super-soft absorbent sweatband for added comfort.



Vented Hard Hat

Ordering Information

Model Number	Description	UPC	Overpack Qty
10036453	Vented Hard Hat, Industrial Grade	641817002780	10

Standards

MSA Safety Works Vented Hard Hats meet or exceed the applicable requirements for a Type I helmet (top impact) as outlined in ANSI Z89.1-1997, Class C (Non-Electrical).

MSA MSA Safety Works®
 MSA World Headquarters • P.O.Box 426
 Pittsburgh, PA 15230-0426 U.S.A.
 Visit us on the Net at: <http://www.msasafetyworks.com>
 Contact via e-mail at: info@msasafetyworks.com

1.800.969.7562 Phone
1.800.969.7563 Fax



**Making The World Safer,
 One Project At A Time.®**

Bulletin SW-06-04 ©MSA 2002 Printed in U.S.A. 0207(L)

NOTE: This bulletin contains only a general description of MSA products and their potential application. Since each application may vary, the need for, and/or type of, safety equipment may also differ. This bulletin describes only typical product applications. A safety professional should be consulted for specific product application recommendations. While uses, applications, and general performance capabilities are described, under no circumstances should the product be used except by trained and qualified individuals and not until complete and detailed instructions concerning these products have been thoroughly read and understood and the precautions therein set forth followed. Only they contain the complete and detailed information concerning these products.