



## MSA Gas Detection System for Transportable Ultima<sup>®</sup> XA Monitor

[ Designed for Transportable Gas  
Monitoring Applications ]

### Application

This custom system monitors 0-3 ppm chlorine dioxide. It has the capability to serve the same markets and facilities as the hard-wired version, excluding combustible gas monitoring applications because of power requirements exceeding the batteries' capabilities.

### Product Description

This Ultima XA monitoring system is transportable, for temporary monitoring in a variety of areas. It is battery-powered, for easy use in locations where an electrical power source is not available. The monitor also has an ON/OFF switch, a horn and a bracket for temporary mounting at the job-site.

Equipped with six AA batteries, the system features a 34- to 36-hour run time under normal conditions, with no alarms activated.

For more information on the standard MSA Ultima XA Gas Monitor see MSA data sheet #07-2051.

*Note: This is a representative description of this product and its potential applications. Contact MSA Custom Products at [customproducts@MSAnet.com](mailto:customproducts@MSAnet.com) for information on customizing this unit to fit a specific need.*



---

**Specifications**

---

**Operating Temperature Range:** - 40° to 140°F (-40 to 60°C)

---

**Power Input:**

Oxygen and toxics: 7-30 VDC

Combustibles: 7-30 VDC @ 450mA maximum

---

**Humidity:** 15-95% RH non-condensing

---

**Relays:** 5 amp @ 220VAC; 5 amp @ 30VDC

---

**Physical:** 1.5 lbs (0.68 kg); 5.125"W x 2.974"D x 9.423" L

---

**Note:** This Data Sheet contains only a general description of the product shown. While uses and performance capabilities are described, under no circumstances should the product be used except by qualified, trained personnel, and not until the instructions, labels or other literature accompanying the product have been carefully read and understood and the precautions therein set forth followed. Only they contain the complete and detailed information concerning this product.

Data Sheet 07-2080  
Sept 2004 (L)  
© MSA 2004 Printed in U.S.A.



Instrument Division:  
P.O. Box 427,  
Pittsburgh PA 15230 U.S.A.  
<http://www.msagasdetection.com>

In U.S.:  
Phone: 1-800-MSA-INST  
Fax: 1-724-776-3280

In Canada:  
Phone: 1-800-MSA-INST  
Fax: 1-416-663-5908

In Mexico:  
Phone: 52 (5) 5 76 64 44  
Fax: 52 (5) 3 59 43 30

MSA International:  
Phone: 412-967-3228  
Fax: 412-967-3373

Offices and representatives worldwide  
For further information:

