

FEATURES	Optional vibrating alarm				X				X	X	X
	Hand-held	X			X	X	X	X	X	X	X
	Pocket-sized				X				X	X	X
	Hands-free operation	X			X	X		X	X	X	X
	Easy-grip design	X	X	X	X	X	X	X	X	X	X
	Pump	X	X	X	X	X	X	X			
	Leak sensor						X				
	Compatible with Link [®] software	X			X	X	X	X	X		
	High RF Protection	X			X	X	X	X	X	X	X
	Rated IP54 or higher	X			X	X	X	X	X	X	X
	Drop tested	X			X	6 ft	X	6 ft	X	6 ft	6 ft
	Lockalarm [™] circuitry	X			x	X	X			X	
	Autocalibration	X			X	X	X	X		X	X
	Rechargeable or alkaline battery packs	X	X	X	X	X	X	X		X	X
FEATURES	Minimum run time	lithium ion 11 hrs, alkaline 6 hrs	8-12 hrs on lithium ion w/hot swap	8-12 hrs on lithium ion w/hot swap	lithium ion 14 hrs	16-20 hrs w/pump	8 hrs (alkaline) 16 hrs (NiMH)	8 hours	24 months	1 year	13 hrs (alkaline) 11 hrs (NiMH)
	Recharging time	less than 6 hrs	less than 4 hrs	less than 4 hrs	less than 4 hrs	less than 4 hrs	less than 4 hrs		less than 4 hrs		3.5 hrs max
	Fresh air setup	X			X	X	X	X	X	X	X
	Pressure-compensated O ₂	X			X	X	X	X			
	MSA leak-proof Button [™] sensor	X			X	X	X	X	X	X	X
	Weight	Less than 1.45 lbs w/ alkaline pack	50 oz w/ batteries	22 oz w/ batteries	less than 8 oz	18.7 oz alkaline w/ pump), 22.6 oz (NiMH w/pump)	less than 29.3 oz		4 oz	4.4 oz	less than 7.7 oz (alkaline), 8.8 oz (NiMH)
	Warranty	1 yr on PID sensor, 2 yrs on other sensors, lifetime on instrument	1 year parts and labor	1 year parts and labor	2 year on all components	2 years on sensor, lifetime on instrument	2 years on sensor, lifetime on instrument	2 years on electronics	24 months on all components	2 years on sensor, lifetime on instrument	24 months on all components