

Constant Flow Air-Line Respirator

[Maintains positive pressure in facepiece]

Ordering Information

Complete Assemblies

Choose facepiece, control valve, and quick-disconnect assembly. Comes with breathing tube and a web support belt. For optional PVC (polyvinylchloride) belt, see Accessories on page 45.

High-Pressure Control Valve (35-40 psig inlet pressure for 8-300 ft of hose)

Quick-Disconnect	Ultra Elite Facepiece	Ultravue Facepiece	Comfo Facepiece	Welder's Comfo Facepiece
Snap-Tite aluminum	810829	460863	460865	460862
Foster steel	810831	480464	480466	480600
Duff-Norton brass	810834	486258	†	†
CEJN Locking chrome-plated brass	810832	480629	480631	480671
Snap-Tite Locking hard-coat anodized aluminum	810833	480633	480635	480672

Low-Pressure Control Valve (10-15 psig inlet pressure for 8-50 ft of hose)

Quick-Disconnect	Ultra Elite Facepiece	Ultravue Facepiece	Comfo Facepiece	Welder's Comfo Facepiece
Snap-Tite aluminum	806775	463300	463302	463281
Foster steel	806776	480472	480474	480468
Hansen brass	806779	484836	484837	†
CEJN Locking chrome-plated brass	806777	480637	480639	480645
Snap-Tite Locking hard-coat anodized aluminum	806778	480641	480643	480646

† Available by special order only. High-pressure control valves are also available with the following special order quick-disconnects: Snap-Tite brass or stainless steel, Foster brass, and Hansen brass, or stainless steel. Low-pressure control valves also available with: Snap-Tite brass or stainless steel, Foster brass, Hansen brass, and Duff-Norton brass. Please call your nearest MSA distributor for complete ordering information.