## NFPA **1801**:

## Standard on Thermal Imagers for the Fire Service



## Overview

The NFPA (National Fire Protection Association)\*, has recently released NFPA 1801: Standard on Thermal Imagers for the Fire Service, 2013 Edition. This new standard provides performance standards for thermal imaging cameras (TICs) used by firefighters on firegrounds and within other hazardous environments. The standard provides requirements for minimum image quality, standard operation, durability, and nonincendive safety. This paper discusses each category and how these requirements impact firefighters.

To meet the new standard, TIC manufacturers must be registered as ISO 9001-compliant. Testing laboratories for TIC NFPA certification must be accredited in accordance with ISO 17025A requirements.

### MINIMUM IMAGE QUALITY

NFPA 1801 requires thermal imaging cameras to meet minimum image quality standards to help ensure that compliant TICs provide information of sufficient quality for fireground use. TIC imaging performance tests conducted include those for image contrast, image spatial resolution and thermal sensitivity.

# STANDARD OPERATING REQUIREMENTS

NFPA 1801 requires that all TICs provide the same interface, enabling firefighters to use any NFPA-compliant TIC with minimal additional training. Requirements include a green power button and an NFPA Basic Mode. Basic Mode limits the camera display to temperature bar, digital temperature readout and heat-indicating color with color reference scale. Any additional camera features must be accessed by taking a *special action* that switches the camera from Basic Mode to Plus Mode. The green power button cannot be used to take this special action, as this distinction is meant to avoid incidence of firefighters potentially accessing features for which they have not been trained.

In addition, powered-on TICs must continuously detect and display images that occur within electromagnetic spectrum range of 8.0 – 14.0 micron. NFPA-compliant TICs must be tested for electromagnetic emission and immunity.

# POWER AND SERVICE LIFE REQUIREMENTS

NFPA-certified TICs, once powered on, must operate continuously for a minimum of 120 minutes in Basic Mode without battery charging or change-out. Operational selection devices such as buttons, keys and switches must be able to be activated using a single gloved hand, and be rated for a 50,000-cycle service life.

### **DURABILITY REQUIREMENTS**

NFPA 1801 has durability requirements to help ensure that TICs are fit for fireground duty. Many of these requirements are similar to those found in NFPA standards for SCBA (self-contained breathing apparatus) and other PPE (personal protective equipment). TIC tests conducted include those for ingress protection, heat/flame resistance, impact acceleration and vibration resistance, and corrosion.

# NONINCENDIVE SAFETY AND ELECTROMAGNETIC REQUIREMENTS

Firefighters sometimes operate within potentially explosive environments; NFPA 1801's intrinsic safety requirement addresses this operational concern. NFPA-compliant TICs must meet ANSI/ISA 12.12.01 Class 1 Division 2 requirements, meaning that TICs are suitable for use within conditions where potentially explosive quantities of dust or vapor may be present.

### **SUMMARY**

NFPA 1801 standardizes TIC operation, helping to ensure minimum image quality, adds nonincendive safety and provides minimum durability requirements for compliant TICs.

NFPA, an international non-profit organization established in 1896, provides consensus codes, standards, research, training, and education concerning fire prevention and minimizing the effects of fire. NFPA 1801 was established to provide minimum design, manufacturing, testing, performance, and certification requirements for fire service thermal imaging cameras. Since its 2010 inception, MSA and other TIC manufacturers have been actively involved in developing the 2013 edition.



# MSA—The Safety Company

Our business is safety. We've been the world's leading manufacturer of high-quality safety products since 1914. MSA products may be simple to use and maintain, but they're also highly-sophisticated devices and protective gear — the result of countless R&D hours, relentless testing, and an unwavering commitment to quality that saves lives and protects thousands of men and women each and every day. Many of our most popular products integrate multiple combinations of electronics, mechanical systems and advanced materials to ensure that users around the world remain protected within even the most hazardous of situations.

Our dedication to safety has been the key to our impressive year-overyear growth. In eight of the past 10 years we've achieved record growth numbers, with annual revenues of more than \$1 billion.

## Our Mission

MSA's mission is to see to it that men and women may work in safety and that they, their families and their communities may live in health throughout the world.

MSA: Because every life has a purpose.

Note: This bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 3460-15-MC / Oct 2012 © MSA 2012 Printed in U.S.A.

### MSA Corporate Center

1000 Cranberry Woods Drive Cranberry Township, PA 16066 USA Phone 724-776-8600 www.MSAsafety.com

### U.S. Customer Service Center

Phone 1-800-MSA-2222 Fax 1-800-967-0398

### MSA Canada

Phone 1-800-672-2222 Fax 1-800-967-0398

### MSA Mexico

Phone 01 800 672 7222 Fax 52 - 44 2227 3943

### MSA International

Phone 724-776-8626 Toll Free 1-800-672-7777 Fax 724-741-1559

### Offices and representatives worldwide

For further information: