


V-Series Tie-Back Lanyards Conversion Guide



ANSI

Complex Worksites. Simplified Solutions.

Our new line of V-Series Tie-Back Lanyards simplifies product selection by offering a concise line of standard lanyards that will meet a wide range of customer needs. All new lanyards shown below also meet the latest ANSI standard for tie-back lanyards: ANSI Z359.13. The tie-back shock-absorbing lanyard uses an FP5K carabiner which can be tied directly back to the lanyard. All tie-back lanyards can be easily identified by the  icon on the energy absorber's cover.

Old P/N	Description	New ANSI P/N	Description	Standard
Legacy Lanyards		V-Series Lanyards		
10107207	FP5K Energy-Absorbing Single-Leg Web Lanyard, 6', tie-back version, 36C snaphook & FP5K snaphook, adjustable	10193560	V-Series tie-back single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphook, FP5K snaphook	ANSI Z359.13, OSHA
10107208	FP5K Energy-Absorbing Twin-Leg Web Lanyard, 6', tie-back version, 36C snaphook & (2) FP5K snaphooks, adjustable	10193941	V-Series tie-back twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphook, FP5K snaphooks	ANSI Z359.13, OSHA



Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA – The Safety Company
1000 Cranberry Woods Drive
Cranberry Township, PA 16066 USA
Phone 724-776-8600
www.MSAafety.com
U.S. Customer Service Center
Phone 1-800-MSA-2222
Fax 1-800-967-0398

MSA Canada
Phone 1-800-672-2222
Fax 1-800-967-0398
MSA Mexico
Phone 01 800 672 7222