



STC383E - Rev 2 - 31.01.05

CERTIFICATION CATEGORY II



# DEXILITE 383

**CE-Type Examination Certificate**  
**0072/014/162/12/96/0681/Ex02 04 97**  
**issued by the approved body nr. 0072**  
I.F.T.H. – Av. Guy de Collongue - F-69134 ECULLY CEDEX

This glove conforms to the provisions of Directive 89/686/EEC for protection against mechanical risks.

57, rue de Villiers - B.P. 190  
92205 NEUILLY SUR SEINE Cedex - FRANCE  
Tél : (33) 1 49 64 22 00 - Fax : (33) 1 49 64 24 29  
[www.mapa-professionnel.com](http://www.mapa-professionnel.com)

**MAPA (U.K.) Ltd**  
Unit A - Halesfield 14 - TELFORD TF7 4QR  
Tel (01) 952 684 487 / Fax (01) 952 580 959

**MAPA®**  
**PROFESSIONNEL**

# DEXILITE 383

## DESCRIPTION AND GENERAL PROPERTIES

**Cotton knit** glove coated with **yellow nitrile rubber**.

**Curved fingers** and **contoured palm**.

**Elastic knitted wrist**.

**Smooth** external surface.

Guaranteed **silicone-free**.

Thickness (in palm area) : **0.80 mm** (nominal value)

Sizes available	Glove length (typical values)
7 - 7 ½	26
8 - 8 ½	27
9 - 9 ½	28
10 - 10 ½	29

Standard packaging :

- **10** pairs in printed polyethylene bag
- **100** pairs per carton

## "CE"-TYPE EXAMINATION RESULTS

### PROTECTION AGAINST MECHANICAL RISKS

Levels of performance according to EN 388 standard



<b>3</b>	<b>1</b>	<b>1</b>	<b>1</b>	
				↳puncture resistance (0 to 4)
				↳tear resistance (0 to 4)
				↳blade cut resistance (0 to 5)
				↳abrasion resistance (0 to 4)

# DEXILITE 383

## SPECIFIC ADVANTAGES

- Cotton lining offers extra comfort : working area totally seam-free.
- Excellent sensivity and flexibility.
- High resistance to abrasion.
- Good protection against splashes of oil and grease.
- Products manufactured in a MAPA factory which is ISO 9001 certified.
- Recommended for persons sensitized to natural rubber proteins.

## MAIN FIELDS OF USE

- Precision engineering
- Painting
- Carpentry
- Preparation of cosmetics
- Packaging
- Parts assembly
- Rubbing down and sanding
- Handling small oily components
- Manufacturing of small electrical components (batteries, lamps...)

## INSTRUCTIONS FOR USE

For enhanced safety and service life of the gloves :

- Store the gloves in their original packaging protected from light and humidity.
- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitized to dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Rub over the gloves contaminated with oil or grease using a dry cloth before taking them off.

Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels.

- Ensure the inside of the gloves is dry before putting them on again.
- Inspect the gloves for snags or tears before reusing them.