

EVOLUTION 5600 TIC

Value-Driven



The Evolution 5600 TIC delivers reliable thermal imaging performance in a value-driven design for firefighters everywhere. This versatile TIC provides detailed images from the vanadium oxide microbolometer sensor, and features a 120 x 120 focal plane array with over 15,000 pixels and a 45° field of view.


MSA's highly functional Heat Seeker and Quick Temp functions are standard and deliver unmatched performance and superior image quality at all temperatures, employing an easy-to-use, time-tested design.

The Evolution 5600 TIC incorporates all of the established user-friendly form factors in MSA's 5000 Series TICs. These features


include single-button activation, patented dual-handle design for ease of handoff, a lightweight lithium ion battery with over two hours of run time, a protective battery compartment, and a comprehensive offering of interchangeable accessories.

As with all MSA TICs, the Evolution 5600 comes standard with a two-year camera core warranty and a one-year warranty on all of the other camera components.

FEATURES	BENEFITS
Heat Seeker Plus	Only MSA offers color pixelization in high- and low-sense modes
Quick Temp	Numerical temperature readout of the scene
Instant on	Camera starts in 2 seconds or less
120 x 120 Focal Plane Array	High performance VOx infrared sensor
High-sense Imagery	Best high-sense imagery; 2 to 4 times longer than competitive cameras



High Sense image detail with Heat Seeker enhancing the heat source with a red isotherm



Low Sense image detail with Heat Seeker enhancing the heat source with a red isotherm

Specifications

Detector	Uncooled Microbolometer Vanadium Oxide (VOx)
Array Format	120 x 120
Pixel Size	38 µm
Spectral Response	7.5 to 13.5 µm
Video Output	NTSC
Frame Rate	30 Hz
NEΔT	≤85mK (in High Sensitivity) ≤350mK (in Low Sensitivity)
Time to Image	< 2 sec.
Scene Temp Range	560°C (1040°F)
Weight	48.2 oz (with battery)
Dimensions	10.8" x 8.1" x 4.4" (HxWxD)
Video Output	RS-170
Operating Time	> 2 hours

Ordering Information

Description

Evolution 5600 complete with Heat Seeker, Quick Temp and User's instruction manual

Part Number

Fahrenheit	Celsius
10097331	10097332

See product specification sheet for more detailed product information.

THERMAL IMAGING KITS:

Fire Station TIC Kit

This kit contains all of the components and accessories that a fire department needs to put their MSA Evolution Thermal Imaging Camera into service. The Fire Station Kit consists of two (2) rechargeable Lithium-Ion Batteries, Single-Unit AC Charger, Retractable Lanyard, Carabiner, Instruction CD and a hard plastic carrying case.



PN 10096887

Vehicle TIC Kit

This kit contains all of the components and accessories that a fire department needs to install their MSA Evolution Thermal Imaging Camera into service on a fire truck. The Vehicle Kit consists of two (2) rechargeable Lithium-Ion Batteries, Universal Truck Charger, Retractable Lanyard, Carabiner, and Instruction CD.



PN10096886

VIDEO TRANSMISSION AND RECORDING SYSTEMS

Mini Receiver Kit

The Mini Receiver Kit enables users to customize your own video monitoring and recording setup. The kit includes a two channel receiver, multiple power cords, and additional adapters packaged in a soft-sided case, with additional room for accessories and the transmitter. Receiver kits come standard with a magnetic mounted, omni-directional antenna.



PN 10050376

Evolution Video Transmitter

Self-contained, modular design allows for maximum flexibility to deploy the transmitter easily when needed. Requires no modification to the TIC. An independent power supply does not draw power from the TIC battery, thus allowing for maximum run time of both TIC and transmission system.



PN 10047573

Deluxe Receiver Kit

The Deluxe Receiver Kit provides users with a complete solution for viewing transmitted images using a single receiver console. The kit features a 12" display that is integrated into the lid of the protective, Pelican case. It comes complete with an omni-directional antenna and wall-type and cigarette-lighter powered supply cords, which can use either 110-220 volt AC, 12 volt, or DC current.



PN 10050375

Evolution Video Capture Kit

Small, easy-to-use, stand-alone video device records screen action of any Evolution 5000-Series TIC for up to 2 hours. Connects in seconds and provides downloadable video clips of fireground for recordkeeping and training.



PN 10071750

ACCESSORIES

Single-Unit Charger

Desktop charger that charges the Evolution Lithium-Ion batteries. Requires 110 or 22 volt AC power supply.



PN 10041100

Non-Charging Universal Truck Bracket

A bracket used to secure the Evolution TIC in a vehicle. System does not have any charging capabilities.



PN 10067707

Universal Truck Charger

Charges any Evolution 5000 Series TIC WITH or WITHOUT the Wireless Transmitter or the Video Capture unit attached. The "smart" Universal Charger trickle charges the battery inside the TIC first, then switches over to the spare battery charging module.



PN 10067565

Reflective Label ID Kit

These HIGHLY REFLECTIVE Write-On Labels will make TIC accountability easier, and provide additional reflectivity on the top and sides of your Evolution 5000 Series. Each Label Kit contains five sets of four labels in bright red, orange, yellow, green and blue. Labels are easily written on with a permanent marker.



PN 10062184

Sun shroud

PN 10039603

Disposable display covers

PN 10038970

Lithium ion battery

PN 10038412

Tripod adapter

PN 10040229

Carabiner

PN 10040005

Plastic carrying case

PN 10040223

Retractable Lanyard

PN 10040226

Shoulder Strap

PN 10039515

Wrist Strap

PN 10039516

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



ID 3400-100-MC / Sep 2008

© MSA 2008 Printed in U.S.A.

Corporate Headquarters
P.O. Box 426, Pittsburgh, PA 15230 USA
Phone 412-967-3000
www.MSAFire.com

U.S. Customer Service Center
Phone 1-877-MSA-FIRE
Fax 1-800-967-0398

MSA Canada
Phone 1-800-MSA-2222
Fax 905-238-4151

MSA Mexico
Phone (52) 55 2122 5770
Fax (52) 55 5359 4330

MSA International
Phone 412-967-3354
FAX 412-967-3451

MSA
The Safety Company