

J42 SINGLE LAYER POLYMERIC SHEET ROOF COVERINGS

To be read with Preliminaries/General conditions.

TYPE(S) OF SYSTEM/EQUIPMENT

130 Cold Roof Covering

Latchways WalkSafe and Access Systems

Latchways have worked with the major roofing manufacturers to produce a range of anti-slip walkways for:

- Standing seam roofing systems
- Membrane roofing systems
- Composite panel roofing systems
- Built-up metal roofing systems
- Secret fix roofing systems

WalkSafe is designed to provide a levelled, anti-slip, delineated walkway surface and affixes to the roof surface in a non-penetrative manner. It is available in 3 configurations:

- Levelled to falls
- Stepped
- Facetted

Latchways WalkSafe has been awarded Agrément Certificate No 99/3608.

The Health and Safety Executive recommends a minimum width of 430mm, or 600mm if materials are to be carried along a walkway.

Single Layer Polymeric Sheet Membrane Roofing

Latchways has developed WalkSafe walkway for use on the single layer polymeric membrane roofing system.

This is a modular system with an anti-slip surface that has been designed and tested to ensure no damage is caused to the roof materials.

The walkway alleviates the standing water problems associated with polymeric single ply membranes by lifting the operative 40mm above the roof finish and provides a stable delineated walkway for access to plant etc.

This also reduces damage and wear and tear to the membrane in regularly trafficked areas.

Consult Latchways plc. technical literature for details. Latchways can also provide a design and specification advisory on the most appropriate walkway solution for each specific application and it is recommended that they are consulted early in the design process.

Additional requirements:

Roof access walkway:

Manufacturer: Latchways plc, Hopton Park, Devizes Wiltshire SN10 2JP Tel: +44 (0)1380 732700

Fax: +44 (0)1380 732701 E-mail: spec@latchways.com Web: www.latchways.com

Product reference: Latchways WalkSafe Roof Walkway and Access System

Components:

Walkway surface: Anti-slip PVC-U planks

Colour: White / Brown / Silver Grey

Support members: 50mm PVC-U cushion bearers

Fixing: Polymeric compatible fixing pad (non-penetrative) – where applicable.