

# V-Series Energy-Absorbing Lanyards

## Conversion Guide



### Complex Worksites. Simplified Solutions.

Our new line of V-Series Lanyards simplifies product selection by offering a concise line of standard lanyards that will meet a wide range of customer needs. All new lanyards shown below also meet the latest CSA standard for energy absorbing lanyards: CSA Z259.11-17.

Old P/N	Description	New CSA P/N	New CSA "Lightweight Worker" P/N	New CSA "Heavy Worker" P/N	Description	Standard
<b>Workman® &amp; Sure-Stop Lanyards</b>		<b>V-Lanyard</b>				
10072474	Workman adjustable single-leg shock-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	10188100	10190397	N/A	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17, OSHA
SWL4068706LS	Single-leg web shock-absorbing lanyard, 1" x 6 ft. (25.4 mm x 1.8 m), 36CL large snaphooks, CSA	10188100	10190397	N/A	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17, OSHA
SNL4048406LS	Single-leg nylon rope shock-absorbing lanyard, CSA	10188100	10190397	N/A	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17, OSHA
SCL4067306LS	Single-leg vinyl-covered cable shock-absorbing lanyard, CSA	10188100	10190397	N/A	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17, OSHA
10073708	Workman twin-leg adjustable shock-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	10188102	10190399	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17, OSHA
SWL40400206LS	Sure-Stop twin-leg shock-absorbing lanyard, 6 ft. (1.8 m)	10188102	10190399	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36C small snaphooks	CSA Z259.11-17, OSHA
10076124	Workman single-leg cable adjustable shock-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	10188103	10190398	N/A	V-Series standard single-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17, OSHA
10072475	Workman twin-leg cable adjustable shock-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	10188101	10190400	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17, OSHA
SWL40400206LSH	Sure-Stop twin-leg shock-absorbing lanyard, 6 ft. (1.8 m), 36C & 36CL snaphooks	10188101	10190400	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17, OSHA
10118779	Sure-Stop twin-leg adjustable nylon web shock-absorbing lanyard, 6 ft. (1.8 m), 36C & 36CL snaphooks	10188101	10190400	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17, OSHA
10118793	Sure-Stop twin-leg adjustable nylon web shock-absorbing lanyard, 36C & 36CL snaphooks	10188101	10190400	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17, OSHA
10118804	Sure-Stop twin-leg cable shock-absorbing lanyard, 36C & 36CL snaphooks	10188101	10190400	N/A	V-Series standard twin-leg adjustable energy-absorbing lanyard, 6 ft. (1.8 m), 36CL large snaphooks	CSA Z259.11-17, OSHA



**WE KNOW WHAT'S AT STAKE.**

## CSA Weight Chart

The below sizing chart reflects MSA's new weight classes for CSA energy absorbing lanyards that meet Z259.11-17.

User Capacity		Previous CSA EA	New CSA EA		
kg	lb.				
45	100	E4 45–115 kg 100–254 lb.	Lightweight CSA 50–105 kg 100–230 lb.	CSA 68–140 kg 150–310 lb.	
50	110				
55	121				
60	132				
65	143				
70	154				
75	165				
80	176				
85	187				
90	198				
95	209	E6 90–175 kg 200–386 lb.			
100	220				
105	231				
110	243				
115	254				
120	265				
125	276				
130	287				
135	298				
140	309				
145	320	Heavy Worker CSA 140–175 kg 310–386 lb.			
150	331				
155	342				
160	353				
165	364				
170	375				
175	386				
180	397				

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



**MSA – The Safety Company**  
1000 Cranberry Woods Drive  
Cranberry Township, PA 16066 USA  
Phone 724-776-8600  
[www.MSAsafety.com](http://www.MSAsafety.com)

**U.S. Customer Service Center**  
Phone 1-800-MSA-2222  
Fax 1-800-967-0398

**MSA Canada**  
Phone 1-800-672-2222  
Fax 1-800-967-0398

**MSA Mexico**  
Phone 01 800 672 7222

ID 2300-210-MC / July 2018

© MSA 2018