

V-SHOCK™ Mini Personal Fall Limiters



Ruggedized

A rugged overmold housing provides unsurpassed durability in abusive environments and cuts down the replacement cycle of units from one project to the next, ultimately saving you money.



Versatility

A swivel eyelet provides better worker mobility and versatility by preventing the tangling of the lifeline and not impeding worker movement.




Lightweight

Weighs just 2.0 lbs. (0.9 kg).
Less weight on the back reduces fatigue and increases productivity.



No External Energy Absorber

The radial energy absorber is protected and sealed off from the outside environment which extends the life cycle of the unit.



WE KNOW WHAT'S AT STAKE.

Ordering Information

Part Number	Type			Line Length	Anchorage Connection	Harness Connection	Standards		
	Single-leg	Twin-leg	Tie-back				ANSI	CSA	OSHA
64011-00A	■			6 ft. (1.8 m)	AL36CL	Steel carabiner	■		■
64011-00ACA	■			6 ft. (1.8 m)	AL36CL	Steel carabiner		■	■
64011-00B	■			6 ft. (1.8 m)	36C	Steel carabiner	■		■
64011-00BCA	■			6 ft. (1.8 m)	36C	Steel carabiner		■	■
64011-00C	■			6 ft. (1.8 m)	Aluminum Swivel Carabiner	Steel carabiner	■		■
64011-00CCA	■			6 ft. (1.8 m)	Aluminum Swivel Carabiner	Steel carabiner		■	■
64011-00F	■			6 ft. (1.8 m)	36CL	Steel carabiner	■		■
64011-00FCA	■			6 ft. (1.8 m)	36CL	Steel carabiner		■	■
64111-00A		■		6 ft. (1.8 m)	AL36CL (2)	Twin-Link Connector	■		■
64111-00ACA		■		6 ft. (1.8 m)	AL36CL (2)	Twin-Link Connector		■	■
64111-00B		■		6 ft. (1.8 m)	36C (2)	Twin-Link Connector	■		■
64111-00BCA		■		6 ft. (1.8 m)	36C (2)	Twin-Link Connector		■	■
64111-00C		■		6 ft. (1.8 m)	Aluminum Swivel Carabiner (2)	Twin-Link Connector	■		■
64111-00CCA		■		6 ft. (1.8 m)	Aluminum Swivel Carabiner (2)	Twin-Link Connector		■	■
64111-00F		■		6 ft. (1.8 m)	36CL (2)	Twin-Link Connector	■		■
64111-00FCA		■		6 ft. (1.8 m)	36CL (2)	Twin-Link Connector		■	■
64041-00A	■		■	9 ft. (2.7 m)	FP5K	Steel carabiner			■
64141-00A		■	■	9 ft. (2.7 m)	FP5K	Steel carabiner			■

V-TEC Mini Twin-Link Connector	
Part Number	Description
64900-00	V-SHOCK Twin-Link Connector



Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



MSA – The Safety Company
 1000 Cranberry Woods Drive
 Cranberry Township, PA 16066 USA
 Phone 724-776-8600
www.MSAsafety.com
U.S. Customer Service Center
 Phone 1-800-MSA-2222
 Fax 1-800-967-0398
MSA Canada
 Phone 1-800-672-2222
 Fax 1-800-967-0398
MSA Mexico
 Phone 01 800 672 7222